

Our NS5100 Series is part of our complete range of anti slip tapes and strips, including barefoot friendly vinyls, conformable, coarse grit, mop friendly, and glow-in-the-dark. Please inquire.

Application Instructions

- Testing of adhesion to surface should be done before installation. Fill in cracks, seal porous surfaces and repair to a smooth finish, as required, avoid application to grout areas.
- Apply to surface that is 50°F (10°C) or higher.
- Always apply No Skidding® Anti Slip Grit Tape to clean, dry, wax and oil free surface.
- Peel off protective release liner and press No Skidding® Anti Slip Grit Tape to prepared surface. Bond is increased by using a rubber hand roller.
- No Skidding® Anti Slip Grit Tape is ready for immediate use, no need to wait.
- Keep No Skidding® Anti Slip Grit Tape clean. Use mild floor cleaners as directed.
- Please read detailed instructions for use before installing.

Please inquire about our full range of anti slip treatments, tapes, coatings and floor care.

Your No Skidding® dealer is:

Technical data and suggestions for use in this brochure are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Any liability we may have with respect to a product or its use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental, punitive or consequential damages. This product cannot eliminate slipping. E&OE

No Skidding®



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: 416-667-1788 • Toll Free: 1-800-375-0571
Fax: 416-667-1783 • www.noskidding.com

No Skidding® is a registered trademark of No Skidding Products, Inc.
We warehouse within the USA for our US customers.

Say goodbye to slippery...

with No Skidding® Anti Slip Grit Tape,
Black, Clear & Colors
NS5100 Series



No Skidding®



FIRST IN ANTI SLIP PRODUCTS SINCE 1993

Say goodbye to slippery...



Colors



Sizes

Rolls

NS5101.....	1" x 60'
NS5102.....	2" x 60'
NS5103.....	3" x 60'
NS5104.....	4" x 60'
NS5106.....	6" x 60'
NS5112.....	12" x 60'
NS5118.....	18" x 60'
NS5124.....	24" x 60'
NS5136.....	36" x 60'
NS5142.....	42" x 60'

Cleats & Treads

3/4" x 24"
5 1/2" x 5 1/2"
6" x 24"

Custom shapes & sizes available.
Please inquire.



NS5100 Series Anti Slip Grit Tape (60 grit) is a hard wearing product designed for application in commerce and industry. Our adhesive system has excellent bonding to clean, sound surfaces with good instant grip.

Recommended for light to heavy traffic areas where wet or slippery floors may expose the user to slip injury.

Consists of a hard wearing aluminum oxide grit profile bonded to a tough substrate. The surface of the tape is resistant to water, grease, detergents and oils.

Simple, quick application. Self adhesive, just peel off the release liner and place into position with firm pressure.

Recommended Uses

- Stairs & Platforms
- Factories & Repair Facilities
- Construction Equipment
- Service Stations
- Loading Docks & Ramps
- Truck Beds & Steps
- Machine Shops & Shipping Areas
- Warehouses & Recreational Areas
- Boats & Yachts
- Farm Machinery
- Forklifts
- Recreational Vehicles
- Step Stools & Ladders
- Buses, Trains & Airline Cargo Areas
- Food Service Areas
- Action Sports
- Numerous Residential Applications



National Floor Safety Institute
certified as "High Traction"

Technical Specifications

- Static Coefficient of Friction on wet and dry surfaces: Exceeds O.S.H.A Requirements
- OSHA Spec 1910.24 Stair Tread
- OSHA Spec 1910.26 Ladder Rungs
- Military Spec Mil-D-17951E-Ships
- Military Spec Mil-W-5044C-Type
- Motor Vehicle Safety Standard #302