

Typical Application

Apartment buildings, hospitals, nursing homes, industrial plants, marinas, schools, offices, warehouses, action sports and various residential applications.

Surface Preparation

Surface must be clean dry and free of contaminants. Clean with No Skidding® Flexclean or On Guard and sand surface if required. If cleaned with No Skidding® Flexclean or On Guard then after cleaning be sure to rinse thoroughly and be sure that the surface has dried completely before applying coating.

Surface should be slightly abraded before application using 000 steel wool or other fine particle size media. As product wears further applications may be necessary. Coating should be steel wool abraded between coats. Clean overspray with acetone. Always test small area before application. Read application instructions on label.

Please inquire about our full range of anti slip treatments, tapes, coatings and floor care.

Your No Skidding® dealer is:

Technical data and suggestions for use in this brochure are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Any liability we may have with respect to a product or its use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental, punitive or consequential damages. This product cannot eliminate slipping. E&OE

No Skidding®



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: 416-667-1788 • Toll Free: 1-800-375-0571
Fax: 416-667-1783 • www.noskidding.com

No Skidding® is a registered trademark of No Skidding Products, Inc.
We warehouse within the USA for our US customers.

Say goodbye to slippery...

with Slip Resistant Textured Acrylic Spray
No. 11935 Clear



No Skidding®

FLOOR SAFETY & MAINTENANCE PRODUCTS



FIRST IN ANTI SLIP PRODUCTS SINCE 1993

Say **goodbye** to slippery...



Slip resistant texture acrylic coating. Spray, product no. 11935C

Theoretical Coverage	20 sq. ft. per aerosol
Vehicle	Acrylic
Weight per spray	1 lb.
Viscosity	Thin liquid
Gloss	Satin
Cleanup	Toluene, Xylene, or Lacquer thinner
% Paint per spray can	45%
Color	Clear
Dry Time	10-20 minutes at 77°F
Recoat	1 hour
Full Cure	24 hrs @ 77°F
Packaging.....	12 X 12 oz. net wt cans per case

No Skidding® Slip Resistant Acrylic Clear Aerosol Spray, Product No. 11935C is a clear acrylic resin blend that air dries rapidly and retains transparency, durability, flexibility and non yellowing characteristics.

11935C is formulated using a recycled plastic particle for enhanced anti slip properties. This product is excellent for increasing traction on steps, ramps, bathtubs, boat decks, diving boards, snowboards, skateboards, surfboards and other sport surfaces where increased traction is needed. Ideal for coating concrete, wood, metal and acrylic surfaces. Suitable for shoe or barefoot traffic. Suitable for interior and exterior use.

Surface Suitability

Concrete, acrylic, wood, fiberglass, steel, aluminum where a slip resistant surface is required. Self priming on most surfaces.

Advantages

- Slip Resistant
- Completely Clear
- Adheres to Most Hard Surfaces
- Economical & Simple Way to Make Small Areas Safe
- Contains Integrated Durable Micro Traction

No Skidding® offer anti slip aerosols in our epoxy series in a range of colors including white, black, gray and safety yellow. 11935 is also available in white. Please inquire.

